WEICAR
High Quality Technical Automotive Technology
TDS (Technical Data Sheet)

Date: 04.09.2026
Revision No: 001
Art No: WC-MP5000Y

Tyre Fitting Paste 5kg

WEICAR Tyre Fitting Paste is a premium mounting compound formulated to facilitate effortless mounting and demounting of vehicle tyres. It creates a pressure-resistant lubricating film between the tyre bead and rim flange, preventing rim slippage, bead damage, and post-installation adhesion or fusing to the rim. It is safe for all standard wheel finishes and does not harm painted, alloy, or polished surfaces.

Areas of Use: Suitable for mounting and demounting of all motor vehicle tyres, including passenger cars, light commercial vehicles, vans, and heavy transport/truck wheels.

Net Weight	4950gr
Gross Weight	5050gr
Volume	5000ml
Package	2pcs
Pallet	160pcs
Pallet Dim	100x120x215h
Appearance & Physical State	Yellow Greasy
Barcode(EAN)	700343203693
Odor	Mild - Characteristic
pH Value	7.5 – 9.0 (neutral to slightly alkaline)



Directions for Use: Ensure rim flanges and tyre bead areas are clean of loose-rust, dirt, and old mounting residues. Apply a uniform, thin layer of WEICAR Tyre Fitting Paste to both the tyre bead and the rim bed using a standard tyre mounting brush. Perform the tyre installation immediately before the paste dries. Allow 5 to 10 minutes after seating for initial flash-off and film stabilizing prior to high-torque road use.

Storage Conditions: Store in the original sealed container in a cool, dry, and well-ventilated area. Protect against frost, direct sunlight, and ambient temperatures exceeding +35°C.
Shelf Life: 36 months from production date when stored in unopened original packaging.

Hazard Pictograms: n/a

In Case of Emergency Consult to MSDS